GIULIANO
AUTOMOTIVE EQUIPMENT



THE REAL "WORK-HORSE" FOR YOUR TYRE SHOP!!

NEW

SX228 PRO

RACING SUPER-AUTOMATIC TILT BACK TYRE CHANGER WITH DUAL ASSIST ARM AND POWER X

YouTube Watch the video

SX228 Pro

www.giuliano-automotive.com



Suitable for **Tubeless** tyre bead seating system (optional).

MADE IN ITALY

Robotic pipe for operating arm positioning/lock.

Motoinverter

MOTOINVERTER
Faster, more accurate and reliable drive for your tyre changer.

Available in 3ph-2 speed, 1ph-2 speed (inverter) and 1ph - 1 speed version

5 YEAR WARRANTY

5 YEAR WARRANTY ON POWERX and GEARBOX

Reinforced Chassis and Tower.

Tilting tower, sliding horizontal arm with Ø 41 mm operating arm.

wdk Approved

Tyre inflation by pedal (standard).

Tools Storage Box (standard).

EXTENSIVE SELECTION OF OPTIONAL ACCESSORIES

Fitting head designed for both standard and low profiled tyre applications.

HP4 Additional auxiliary helper system (standard) provides a valuable support in mounting/demounting Run Flat, UHP and low profiled tyres.


POWERX grants **double** (uniform) clamping power on jaws, and an almost endless durability and reliability of your turntable!!! [Giuliano Patent].



Additional tilting roller tool for lower bead with an anti-collision joint.

Tabletop thickness 14 mm w/**POWER X** four cylinders clamping system [**Giuliano Patent**].

Patented **PO SYSTEM** (standard) **automatically** moves the bead breaker shovel back to the starting position, after its penetration.



A very practical **Wheel Lifter** reduces effort and increases productivity (optional).

Bead breaker double effect Cylinder Ø 200 mm.

Double rotation speed by pedal.

Intensive use

400V-3ph 2V

Adjustable bead breaker shovel stroke.



"Easy Access" extractable pedal box for quick service.

STANDARD FEATURES

Rim clamping from outside	10" - 27"
Rim clamping from inside	12" - 29"
Max. tyre diameter	1100 mm (43")
Max. tyre width	415 mm (16")
Bead breaker cylinder force at 10 Bar	30800 N
Operating pressure	10 bar (145 Psi)
Power supply	400V-3ph-2 speed 220V-1ph/220V-1ph-2 speed
Motor power	0,8 / 1,1 kW (3 ph)
Rotation speed	7 - 14 rpm
Pre-set tyre inflating pressure	3,5 bar (50 Psi)
Net weight	360 kg
Max. overall dimensions	1590x1930x2040 mm

STANDARD ACCESSORIES



• Bead lifting lever • Lube paste bucket and Brush • Plastic protectors for mounting/demounting tool • 2 Protectors for bead breaker shovel • Jaw protectors for alloy rims • Lubricator + Pressure regulator • Bucket support

GROUP GIULIANO S.p.A.

DESIGNED, BUILT & ENGINEERED IN ITALY